

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-105484

(43)Date of publication of application : 11.04.2000

(51)Int.Cl.

G03G 9/08
G03G 9/087
G03G 15/20

(21)Application number : 10-274667

(71)Applicant : FUJITSU LTD

(22)Date of filing : 29.09.1998

(72)Inventor : TAKAHASHI TORU
NAKAMURA YASUSHIGE

(54) ELECTROPHOTOGRAPHIC TONER AND IMAGE FORMING METHOD

(57)Abstract:

PROBLEM TO BE SOLVED: To provide an electrophotographic toner and image forming method by which excellent wear resistance of the surface of a fixed image can be obtd. regardless of the fixing method.

SOLUTION: This toner consists at least of a binder resin and coloring agent. The breaking load of the toner is controlled to ≥ 100 gf, and the coefft. of static friction on the surface of an image transferred and fixed to a recording medium is controlled to ≤ 0.4 . The image forming method using the heat roll fixing method for image fixing uses the combination of a recording medium and the toner which is comprised at least of a binder resin and coloring agent and which shows ≥ 100 gf breaking load and ≤ 0.4 coefft. of static friction on the surface of an image transferred and fixed to the recording medium.

LEGAL STATUS

[Date of request for examination] 19.06.2001

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C): 1998,2000 Japanese Patent Office